

HDMI SWITCHERS

KD-S4x1X-2

4 Input Slim Series HDMI Auto Switcher



SPECIFICATIONS

- » Input (Each): HDMI Connector, Type A, 19 Pin Female
- » Output: HDMI Connector, Type A, 19 Pin Female
- » Bandwidth: TMDS bandwidth 18 Gbps
- » DDC Signal (Data): Input DDC Signal - 5 Volts p-p (TTL)
- » HDMI Video/Audio Signal: Input Video Signal - 1.2 Volts p-p
- » Power Supply: KD-PS5V1ASC, 5V/1A, 100-240VAC, 50-60Hz, Interchangeable head, screw-in connector
- » Regulation: CE, RoHS, WEEE, EAC
- » Enclosure: Black Metal
- » Product Dimensions: 7.7 x 3.5 x 0.8" (197 x 90 x 20mm)
- » Packaging Dimensions: 9.4" x 5.6" x 3.1" (240 x 144 x 80mm)
- » Product Weight: 0.9 lb
- » Shipping Weight: 1.3 lb

ACCESSORIES

- » Power Supply (qty 1): 5V/1A, 5W, wall type, model SK01T-0500100Z
- » IR Remote Control: KDRMSWPROK
- » Mounting Brackets: 2 L-shaped
- » Control Cable: 6ft RS-232 3.5mm TRS to Micro USB, KD-S2x1XUSB2RS

SYSTEM DESIGN EXAMPLE

