KD-VW4x4Pro

4x4 Outputs Video Wall Processor, supports Seamless Matrix Switching

KEY FEATURES

- HDMI Matrix Switching: 4 HDMI/Analog sources to 4 HDMI outputs, independent when in matrix mode
- > Seamless Switching: Un-interrupted screen transitions during source selections
- Video Wall Processing: Transform consumer and professional displays into a video wall with eight video wall modes:
 - » Horizontal (4): 1x4 Rotated, 1x4, 1x3, and two sets of 1x2
 - » Vertical (3): 4x1, 3x1, and two sets of 2x1
 - » 2x2
- > Bezel Control: Create a fluid screen transition by removing pixels from top, bottom, left, and right border independently
- > Panel Flip: Enables use of consumer displays by mounting top row upside down
- Resolution Support: Supports SD, HD, and VESA input resolutions up to 1080p / 1920x1200 on HDMI and analog video Inputs
- EDID: Internal library with 5 default EDID configurations for each input, in addition to native EDID data for any Output/Display
- > Full Buffer[™] Technology: Full buffering of HDCP and EDID, for the fastest possible switching and viewing of any source/input to any display/output, regardless of multiple output viewing relation
- TMDS re-clocking: Support for long HDBaseT/CAT5e/6 or HDMI connections and many layers of connectivity.
- > Deep Color Support: Up to 12 bits/color

MANAGEMENT SOFT

- Control: Front panel buttons, Serial IR, Optical IR, RS-232, and TCP-IP, including video wall mode select, matrix switching, EDID Control and discrete on and off via IR
- Control System Support: Compatible with Compass Control[®] Pro, AMX[®], Control4[®], Crestron[®], KNX[®], RTI[®], Savant, URC[®], Leviton[®], etc.

SPECIFICATIONS

- » Input (Each): 1 HDMI connector, Type A, 19 pin female; 1 HD analog video 15-pin female, 1 analog audio connector, 3.5mm stereo female
- » Output (Each): 1 HDMI connector, Type A, 19 pin female
- » Power Supply: KD-PS12V3A, 12V/3A, 100-240VAC, 50-60Hz, NEMA 1-15P Cord
- » Rack Mount: 1U, full rack-width (rack ears included)
- » Product: 17.25" x 7.1" x 1.75; Weight: 6.5 lbs
- » Packaging: 22.8" x 8.5" x 3.2"; Weight 8 lbs
- » Regulation: CE, RoHS, WEEE, EAC
- » Enclosure: Black Metal





SYSTEM DESIGN EXAMPLE

KEY DIGITAL*