

KD-X4x1WUTx

4x1 4K/18G 100m HDBT PoH Wall Plate Switcher with 2x HDMI, DP, USB-C, USB, LAN, ARC, Audio De-Embed, IR, RS-232, IP Control, CEC Manager™. Transmitter Only.

KEY FEATURES

- ▶ **Presentation Switching:** 2 HDMI, 1 Display Port, and 1 USB-C source selection by push button or IP control.
- ▶ **Rx Options:** Native integration with KD-X100MRx black box HDBaseT Rx, KD-UPS52U and KD-UPS72U Presentation Switchers. Other Rx options available.
- ▶ **Soft-Codec Enabling System:** USB Host + Device ports on wall plate and chosen Rx / Presentation Switch create connectivity hub for professional USB cameras and microphones, audio DSP, keyboard, mouse, or touchscreen display with connected computer
- ▶ **PTZ USB Camera Integration:** Marries natively with KD-CAMUSB for full PTZ control via KD-App and more
- ▶ **Ultra HD/4K:** Supports up to 4096x2160 or 3840x2160 24/25/30/60hz at 4:4:4 (signals up to 18Gbps bandwidth)
- ▶ **Auto-Sensing:** Automatic selection of newly detected source and switching from newly disconnected source when enabled
- ▶ **CEC Manager™:** Power, volume, and muting controls of the connected displays/projectors without any additional control wiring.
- ▶ **Audio De-embedding:** Audio of the selected source is de-embedded at the unit's analog L/R balanced/unbalanced connector
- ▶ **HDCP Licensing:** Fully licensed and compatible with HDCP 2.2
- ▶ **HDR10 & Dolby Vision:** More life-like images through a greater range of luminance levels
- ▶ **Power Over HDBaseT:** Wall-plate unit powered by Rx/Presentation Switch unit
- ▶ **Installation:** Tx unit designed for installation in standard US three-gang box
- ▶ **Signal Extension:** For resolution and cable quality
 - » 4K/UHD (18G): Up to 100m / 328ft
 - » 1080p: Up to 150m / 492ft
- ▶ **Deep Color Support:** Up to UHD/4K 30Hz 4:4:4/12 bits or 60Hz 4:4:4/8 bit
- ▶ **Full Buffer System™:** Manages TMDS re-clocking / signal re-generation, HDCP authentication to source & display, EDID Control handshake, and Hot Plug Detection Voltage
- ▶ **EDID Management:** Internal library with 15 internal EDID handshakes including 4K with HDR in addition to native EDID data copied from the Rx display/device
- ▶ **IR Sensor:** Wall-plate collects line-of-sight IR from remote(s) without external IR wiring



- ▶ **RS-232:** Bi-Directional control to/from Tx and Rx/Presentation Switch unit
- ▶ **Unit Control Mode:** Provides TCP/IP and RS-232 control and status of/from Tx unit
- ▶ **Lossless compressed digital audio:** Support for Dolby® TrueHD, Dolby® Digital Plus, Dolby Atmos®, and DTS-HD Master Audio™
- ▶ **Control System Support:** Fully controllable by all TCP/IP and RS-232 supported control systems via open API: Compass Control® Pro, AMX®, Crestron®, KNX®, RTI®, Savant, URC®, Leviton® etc.
- ▶ **KD-App Ready:** Network scan & detect populates pre-built GUI including connected display/projector controls via CEC Manager™

SPECIFICATIONS



- ▶ Regulation: CE, RoHS, WEEE, EAC
- ▶ Wallplate: Standard 3-gang Wallplate
- ▶ Enclosure: Faceplate - Silver Brushed Metal, Body - Texturized Silver Metal
- ▶ Product: 5.5 x 4.1 x 1.43" (141 x 105 x 36.4mm); Weight: 1.3 lbs
- ▶ Packaging: 11" x 7.9" x 2.1" (280 x 200 x 55 mm); Weight: 2.1 lbs

SYSTEM DESIGN EXAMPLE

